


SPOT ELEVATIONS KEY:

- ⊕ = EXISTING GRADE
- +0 = PROPOSED GRADE



PROJECT NOTES:

1. Provide wider joint spaces at bottom of planter walls to allow for drainage. Use filter fabric over the joint openings to prevent soil from washing out.
2. All step treads are to be 15" deep unless otherwise specified. Riser heights are shown on drawing.
3. Walls are to be made of brussels block dimensional material. Color to be approved by homeowner. Use brussels block cap material.
4. Pavement to be Unilock Beacon Hill flagstone.
5. Provide irrigation for all planting areas.
6. Provide PVC sleeves under the paving to allow for irrigation lines and electric lines to run under the pavement.
7. Provide a sheet metal firepit cover and/or provide a drain at the bottom of the firepit.
8. Contractor to call Miss Dig to identify underground utilities before construction.
9. Handrail can be transparent either using a glass hand rail or galvanized steel cable wire with posts.
10. All pavement to slope min of 2% away from house.
11. Provide step lighting under step risers. Consult homeowner for additional lighting in other areas such as in the firepit area.

Tagsold Residence

11574 Round Lake Dr. Manitou Beach, MI 49253

Conceptual Landscape Design

Scale: 1 inch = 8 feet

Date: May 7, 2015 Revised: MAY 22, '15, MAY 27, '15

By: Cynthia Fink for TERRAFIRMA

Landscape Architect

734-646-8382